




Series 640


Page 2 of 2


SHOP DRAWINGS














INFORMATION

Width Custom made to any width
Height Custom made to 10' -1"
Panels Aluminum: Solid or Perforated

Side Channel Aluminum: Clear
Panel Connector Flexible Vinyl: Clear

Coordinated with side channel

Hinge System Steel: Clear

Wheels Ball bearing nylon wheels on steel axles
Track Aluminum (straight or curvable): Clear
Recessed Channel/ Aluminum (straight only): White

"Hat" Channel

Lead, Intermediate and Jamb
Aluminum: Clear
Thumb Turn two sides
Header
Construction Details by Others
Door Weight
Average W

 Height
 Average Weight

 6'-8"
 10lbs. Per lineal foot

 8'-1"
 12lbs. Per lineal foot

 10'-1"
 15lbs. Per lineal foot

<u>Catch/Lock Options</u>

Magnet with strike plate

Privacy Latch Deadlatch with thumb turn one side
Springlatch Springlatch with thumb turn two sides

Keylock 1 Side Deadlatch with thumb turn one side, keylock one side

Key and Single Bolt Key and single bolt lock
Key and Double Bolt Key and double bolt lock

Single Cremone Bolt with Key Lock
Double Cremone Double Cremone Bolt with Lock

Footbolts Locking or non locking

Other Keyed Options Keyed alike, custom keyed, construction core

Contact manufacture for more details

See Woodfold Accordion Door brochure for additional details

Job Name:	Architects Acceptance
Job Location:	
Supplier:	

Qty. Single/Pair Single End/Double End Left or Right Stack Width X Height Finish/Color	Comments

THESE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

Woodfold Manufacturing. Inc. P.O. Box 346 Forest Grove, OR. 97116 http://www.woodfold.com

Phone: 503-357-7181 Fax: 503-357-7185

640 SD 6/03